

NOTES:

*Because of our ongoing commitment to quality and innovation, we reserve the right, at any time, to discontinue or change specifications, designs, features, models, or equipment without incurring obligation.

**Not all tracks can be installed on all sleds without modification. The listings in the application chart fit OEM suspension, track width, length, and drive pitch only. To determine if an optional track is compatible with a particular snowmobile, you must check the bulkhead, tunnel, heat exchanger, and suspension wheel positioning for proper clearance.

***See your dealer for installation procedures.



Snowmobile Make and Model	Year(s)	Width in.	Length in.	Lug in.	Pitch in.	Track Model	Application Notes	Replacement
Polaris								
x 340 & 340 LX	08	15	121	.82	2.52	Lightning		
x 340 LX	07	15	121	.66	2.52	Lightning		
340 Touring	04-07	15	136		2.52			
340 Touring	99-03	15	133.5		2.52		use 136 track - modifications required	
340 & 550 TransPort - see TransSport below								
x 550 LX	07-08	15	121	.82	2.52	Lightning		
x 550 IQ LXT	11	15	136	1.0	2.52	Hack Saw		9010H / 9010H162
x 550 IQ Shift (inc. ES)	09-11	15	121	.91	2.52	Shockwave		
x 550 Shift 136	11	15	136	1.25	2.52	Shockwave		
x 600 Dragon IQ (including SP)	08-09	15	121	1.25	2.52	Rip Saw		
x 600 HO IQ (inc. CFI)	07	15	121	1.0	2.52	Shockwave		
x 600 HO IQ LX CFI (M-10 suspension)	07-08	15	128	1.0	2.52	Hack Saw		
x 600 HO IQ Touring	09-10	15	136	1.0	2.52	Hack Saw		9010H / 9010H162
x 600 IQ (inc. ES)	09-10	15	121	1.0	2.52	Hack Saw		
x 600 IQ LXT	11	15	136	1.0	2.52	Hack Saw		9010H / 9010H162
x 600 IQ Shift (inc. ES)	11	15	121	.91	2.52	Shockwave		
x 600 IQ Shift (see also IQ Shift below)	09-10	15	121		2.52			
x 600 IQ Shift 136	09	15	136	1.0	2.52	Hack Saw		9010H / 9010H162
x 600 Shift 136	11	15	136	1.25	2.52	Shockwave		
x 600 IQ Touring	08-09	15	136	1.0	2.52	Hack Saw		9010H / 9010H162
x 600 LX	10	15	136	1.0	2.52	Hack Saw		9010H / 9010H162
600 RMK - see RMK below								
x 600 RR (racer replica)	08	15	121	1.25	2.52	Rip Saw		
x 600 Rush & 600 Rush LX	11	15	121	1.0	2.52	Hack Saw		
x 600 Rush Pro-R	11	15	121	1.25	2.52	Rip Saw		
x 600 Rush & Rush ES	10	15	120	1.25	2.86	Rip Saw	2-ply Rip Saw; track changed after early sales literature was printed	
x 600 Widetrak IQ	10	20	156	1.25	2.52	Rip Saw Full		9002U
x 700 Dragon IQ	08	15	121	1.25	2.52	Rip Saw		
x 700 IQ	08	15	121	1.0	2.52	Hack Saw		
700 RMK - see RMK below								
x 800 Assault RMK 146	09-10	15	146	2.125	2.86			
x 800 Dragon IQ (including ES & SP)	08-10	15	121	1.25	2.52	Rip Saw		
x 800 IQ (inc. ES)	09-10	15	121	1.0	2.52	Hack Saw		
800 LE	01	15	121		2.52			
x 800 Rush	11	15	121	1.0	2.52	Hack Saw		
x 800 Rush Pro-R	11	15	121	1.25	2.52	Rip Saw		
800 RMK - see RMK below								
x 800 Switchback Assault - see Switchback below								
Assault - see 800 Assault RMK above								
x Classic (all ex. 06 700, some w/M-10 susp.)	93-06	15	121		2.52			
x Classic 700 (M-10 suspension)	06	15	128	1.25	2.52			
Classic 500	92	15	133.5		2.52			
Classic 500	89-91	15	121		2.52		use 136 track - modifications required	
Classic Touring 500, 600 & 800	93-03	15	133.5		2.52		use 136 track - modifications required	
Classic Touring 700	03	15	136		2.52			
x Dragon 700	07	15	121	1.25	2.52	Rip Saw		
Dragon RMK 700	07	15	155		2.86			9104M
Dragon Switchback - see Switchback below								
Edge Touring (all)	04-05	15	136		2.52			
Frontier Classic (4-stroke)	03-04	15	121		2.52			
Frontier Touring (4-stroke)	03-05	15	136		2.52			
x FS Classic (M-10 suspension)	06	15	128	1.25	2.52			
x FS IQ Touring	06-09	15	136	1.0	2.52	Hack Saw		
x FST Classic (M-10 suspension)	06	15	128	1.25	2.52			
x FST IQ	07	15	121	1.25	2.52	Rip Saw		
x FST IQ Cruiser (see also IQ Cruiser)	07	15	136	1.0	2.52			
x FST IQ LX (M-10 suspension)	07	15	128	1.0	2.52	Hack Saw		
x FST IQ Touring	06-10	15	136	1.0	2.52	Hack Saw		
x Fusion (all)	05-06	15	121	1.25	2.52			
Indy 340 (inc. Deluxe)	99-04	15	121		2.52			
Indy 400 (inc. 88 Classic 400)	85-91	15	121		2.52			
Indy 440	92-98	15	121		2.52			
Indy 440 SKS	93-95	15	133.5		2.52		use 136 track - modifications required	
Indy 500 (inc. EFI & SP) see Classic 500 ab	89-06	15	121		2.52			
Indy 500 triple (Centurion)	81-82	15	121		2.52			
Indy 500 SKS (inc. EFI)	90-96	15	133.5		2.52		use 136 track - modifications required	
Indy 600 (inc. SE & LE)	83-87	15	121		2.52			
Indy 650	88-92	15	121		2.52			
Indy 650 SKS	90	15	133.5		2.52		use 136 track - modifications required	
Indy Classic - see Classic above								
Indy Lite (inc. Deluxe)	93-98	15	121		2.52			
Indy Lite (inc. Deluxe)	91-92	15	116		2.00		no track available	NA
Indy Lite GT & Indy Lite Touring	91-98	15	133.5		2.52		use 136 track - modifications required	
Indy RXL - see RXL below								
Indy Sport - see Sport below								
Indy StarLite	93-95	15	121		2.52			
Indy StarLite	91-92	15	116		2.00		no track available	NA
Indy StarLite GT	93-95	15	133.5		2.52		use 136 track - modifications required	
Indy Storm - see Storm below								
Indy SuperTrack (inc. Trail SuperTrak)	89-92	15	156		2.52			
Indy Trail - see Trail below								
Indy Widetrak - see Widetrak below								
Indy XCR - see XCR below								
Indy XLT - see XLT below								
IQ - see 800 HO IQ, FS & FST IQ above								
x IQ Cruiser (see also FST IQ Cruiser)	08	15	136	1.0	2.52	Hack Saw		9010H / 9010H162
x IQ Shift (also see 550 IQ & 600 IQ above)	08-10	15	121	.91	2.52	Shockwave		
x IQ Turbo Dragon	08-10	15	121	1.25	2.52	Rip Saw		
x IQ Turbo LX (M-10 suspension)	08	15	128	1.0	2.52	Hack Saw		
IQ Widetrak - see Widetrak below								
Longtrak (inc. LongTrak Reverse)	85-89	15	148		2.52			
x Pro-RMK 800 - see RMK 800 below								
Pro X (all except 120)	03-04	15	121		2.52			
Pro X2 (all)	04	15	121		2.52			
Pro XR 800	04	14	121		2.52			
RMK 500 (inc. EFI)	96-99	15	133.5		2.52		use 136 track - modifications required	
RMK 500, 600, 700 & 800 / 136	00-02	15	136		2.52			
RMK 600 & 700	97-99	15	136		2.52			
x RMK 600 / 144	11	15	144	2.0	2.86	Series 4		
RMK 600 (inc. Dragon, ES & HO), 700, 800	01-10	15	144		2.52			
x RMK 600 / 155	11	15	155	2.4	2.86	Series 5.1		
x RMK 600 (inc. Dragon, ES, HO & Shift) / 15	07-10	15	155	2.5	2.86			9104M
x RMK 700 (inc. Dragon & ES) / 155	08-10	15	155	2.5	2.86			9104M
RMK 700, 800 & 900 / 151	01-06	15	151		2.52			
RMK 700, 800 & 900 / 159	04-06	15	159		2.52			
x RMK 700 / 163	08	15	163	2.5	2.86			9105M
RMK 800 (inc. ES & Shift) / 144	09-10	15	144		2.52			
x RMK 800 / 155	11	15	155	2.4	2.86	Series 5.1		
x RMK 800 (inc. Dragon & ES) / 155	08-10	15	155	2.4	2.86	Series 5.1		9104M

